

22 Foot Wide Gutter Connect Greenhouse

- Expandable structure
- More growing space
- Structural aluminum gutters
- Tensile strength of 50,000- 55,000 PSI
- Gutter has base extruded into the aluminum gutter
- Tubing is Allied Gatorshield Steel

		48 Foot long	72 Foot Long	96 Foot Long	128 Foot Long
Frame with 8 Foot High Gutters	1 Bay	\$ 4,707	\$ 6,752	\$ 8,409	\$ 10,749
	Additional Bay	3,373	4,765	5,956	7,616
Cover with 8 Foot High Gutters	1 Bay	1,637	2,179	2,255	2,748
	Additional Bay	551	689	880	1,062

		48 Foot long	72 Foot Long	96 Foot Long	128 Foot Long
Frame with 10 foot High Gutters	1 Bay	\$ 5,660	\$ 8,028	\$ 10,020	\$ 12,789
	Additional Bay	3,970	5,529	6,899	8,785
Cover with 10 Foot High Gutters	1 Bay	1,919	2,582	2,681	3,306
	Additional Bay	551	689	880	1,062

Specifications

Engineered for 20 Pound Roof Load

- Column Post Spacing 8 Foot
- Height to Gutter 8 or 10 Foot
- Arch Spacing 4 Foot
- Purlins 3, 1-3/8" OD / 16 Gauge
- Wind Braces 4, 1-3/8" OD / 16 Gauge
- Column Post, 8 Foot Gutter: 2" round OD / 13 Gauge
- Column Post, 10 Foot Gutter 2-1/2" square OD / 12 Gauge
- Arch 1-5/8" OD / 14 Gauge
- End Wall Posts 1-5/8" OD / 14 Gauge
- End Wall Bracing 1-5/8" OD / 14 Gauge
- Gutter 10" Aluminum Extruded
- Cross Tie 1-3/8" OD / 16 Gauge

